



Download from
Dreamstime.com

This watermarked comp image is for previewing purposes only.



ID 35103813

© Yulia Gapeenko | Dreamstime.com

[Steamapiregistercallresult](#)

Select the correct file here

Click to upload firmware to modem

Set to appropriate COM port for the PC used

Set Baud Rate to 19200

The screenshot shows the 'LPC2000 Flash Utility V2.2.3' window. The 'Flash Programming' section has a 'Filename' field containing 'S:\FLASHing\2F700GXB5.hex' and an 'Upload to Flash' button. The 'Communication' section has a 'Connected To Port' dropdown set to 'COM1' and a 'Use Baud Rate' dropdown set to '19200'. The 'Device' section has a 'Device' dropdown set to 'LPC2136' and an 'XTAL Freq. [kHz]' field set to '20000'. A 'Read Device ID' button is also visible. Red arrows point from the text annotations to these specific fields and buttons.

Set crystal frequency to 20000

Click to establish communication with the modem

[Steamapiregistercallresult](#)



Download from
Dreamstime.com

This watermarked comp image is for previewing purposes only.



ID 35103813

© Yulia Gapeenko | Dreamstime.com

100% working Best video how to fix error the program can't start because steam_api.dll is missing from your ...

6aa8f1186b